



FUNGISTOP

Ready-to-use, broad spectrum, solvent-borne wood preservative.

7.2

Pages: 3
1 - 2017



Description

Ready to use, solvent-borne wood preservative for timber out of ground and water contact. It protects timber against wood rotting and blue stain fungi, insects and termites, enhancing the adhesion properties of subsequent surface coating. The product is made for outside application on wooden surfaces, such as Windows, exterior doors, claddings, eaves, fences, carports etc.

Purpose of Use

Protection of wooden surfaces. It can be used on external wood components, such as windows, exterior doors, cladding, fences, eaves and carports. Not for use for indoor surfaces, for wood that comes into direct contact with food and animal feeding stuff, or wood in contact with soil or in marine environment.

Product Characteristics

- > Solvent based.
- > For outdoor use.
- > Ready to use.
- > Broad spectrum protection against wood destroying and blue stain fungi (according to European Standards as the EN 113, EN 46, EN 118, EN 84, EN 73, EN 152).
- > Colorless.
- > Does not alter the shade of the wood.
- > Suitable for amateur and professional use.
- > Easy to apply.
- > Product Registration Number TP18-0068.

Shades

Available colorless.

Coverage

Theoretical coverage 200ml/m².

Recommended Painting Systems

Old and new surfaces	The product is applied on new surfaces. The use of the product on old, already painted surfaces is not recommended.
Recommended fields of application	External wood components, such as windows, exterior doors, cladding, fences, eaves and carports. Not for indoor use. To be surface coated with a top coat for exterior use according to the use recommendations provided with that product.

Packing:
0,75lt / 2,5lt



Bases:
—



Stir well before use



Coverage:
200ml/m²



Drying time:
Touch dry after
1 to 2 hours



Application:
With roller



Application:
With brush



Application conditions

When applying, the wood moisture should not exceed 18% and the wood surface should be clean, dry and free from decay at the time of treatment. During application and drying, the temperature should be above 5°C and the relative humidity should be below 80%. Cover the ground with a plastic sheet during outdoor application. Do not apply where the product during the application can reach surface waters as e.g. a bridge over.

Application Instructions

The product is ready-to-use and should not be diluted. Stir thoroughly prior to use. Close the container tightly after use. Apply with brush or roller. Cleaning of tools should be done with white spirit.

Surface Preparation

The surface to be painted should be completely dry and clean.

Technical Characteristics

Coverage	200ml/m ² .
Thinning	The product is ready to use and no thinning is required.
Application	Applied by brush or roller.
Non volatile content	6-10% w/w.
Drying time	Touch dry from 1 -2 hours.
Recoating	Drying time to handle and recoat is approximately 24 hours (at 23°C and 60% relative humidity).

Packing:
0,75lt / 2,5lt



Bases:
—



Stir well
before use



Coverage:
200ml/m²



Drying time:
Touch dry after
1 to 2 hours



Application:
With roller



Application:
With brush



Storage

Keep only in the original container. Keep in a safe place. Keep out of the reach of children. Keep away from sources of ignition - No smoking. Keep container tightly closed in a well ventilated place. Store between 5 - 25°C. Keep from frost. Do not contaminate water, food, or feed by storage or disposal.

Instructions precautions - Prevent environmental impact

Read the label before use. Keep out of reach of children. Avoid contact with eyes or skin. Keep away from food, drinks and animal feeding stuff. Use the product only as wood preservative and as described on the label. Rinse immediately with water in case of contact with eyes or skin. Wash hands and exposed skin before meals and after use. Use protective clothing, gloves, eye/face protection and respiratory protection if needed. Avoid release to the environment. Dispose of contents and container in accordance with all local, regional, national and international regulations. Cover the ground with a plastic sheet during outdoor application. Do not apply where the product during application can reach surface waters (such as bridge over pond). Do not use the product indoors. For more information ask for the Material Safety Data Sheet.

Use biocides safely.

Always read the label product information before use.

Packing:
0,75lt / 2,5lt



Bases:



Stir well
before use



Coverage:
200ml/m²



Drying time:

Touch dry after
1 to 2 hours



Application:

With roller



Application:

With brush



All the above information is based on laboratory tests and long-term experience of the company's scientific personnel. Product quality is guaranteed by our operational system, which is based on the requirements of ISO 9001 and ISO 14001 Standards and EMAS Regulation. As producers we don't take any responsibility for any damage that may be caused in cases that the product hasn't been used for the appropriate application and according to the application instructions.

Page 3 of 3
117082/V1

BERLING SA
Paint Industry

Inofita Viotias, P.C. 32011
tel.: +30 22620 31663, fax.: +30 22620 31293
www.berling.gr / info@berling.gr


Color has a Name!