

## **GG9000FE**PETROL GENERATOR





















NOMINAL POWER	7,0 Kw
MAXIMUM POWER	7,5 Kw
FREQUENCY	50 Hz
VOLTAGE	230 v
INTENSITY	30,4 A
OUTPUTS	1 x 32A / 1 x 16A
DISPLAY	Analogic
BATTERY (Ah)	14 Ah
FUEL TANK CAPACITY	25 L
DC OUTPUT	12V / 8,3A
CONSUMPTION AT 50% OF THE LOAD	1,4
AUTONOMY AT 50% OF THE LOAD	18 h
SOUND LEVEL AT 7 METERS (dBA)	78
MOTOR MODEL	IC460E
MOTOR MODEL	
ENGINE POWER	16 HP
	16 HP Electric / Recoil
ENGINE POWER	
ENGINE POWER START	Electric / Recoil
START CYLINDER	Electric / Recoil 459 cc
ENGINE POWER START CYLINDER OIL CAPACITY (L)	Electric / Recoil 459 cc 1,6 L
START CYLINDER OIL CAPACITY (L) ALTERNATOR	Electric / Recoil 459 cc 1,6 L A7L
ENGINE POWER  START  CYLINDER  OIL CAPACITY (L)  ALTERNATOR  NOMINAL POWER	Electric / Recoil 459 cc 1,6 L A7L 7 kW
ENGINE POWER  START  CYLINDER  OIL CAPACITY (L)  ALTERNATOR  NOMINAL POWER  POWER FACTOR (Cosp)	Electric / Recoil 459 cc 1,6 L A7L 7 kW
ENGINE POWER  START  CYLINDER  OIL CAPACITY (L)  ALTERNATOR  NOMINAL POWER  POWER FACTOR (Cosp)  VOLTAGE REGULATION	Electric / Recoil 459 cc 1,6 L A7L 7 kW 1 AVR / Brush
ENGINE POWER  START  CYLINDER  OIL CAPACITY (L)  ALTERNATOR  NOMINAL POWER  POWER FACTOR (Cosp)  VOLTAGE REGULATION  LOW OIL PRESSURE	Electric / Recoil 459 cc 1,6 L A7L 7 kW 1 AVR / Brush SI
ENGINE POWER  START  CYLINDER  OIL CAPACITY (L)  ALTERNATOR  NOMINAL POWER  POWER FACTOR (Cosφ)  VOLTAGE REGULATION  LOW OIL PRESSURE  OVERLOAD INDICATOR	Electric / Recoil 459 cc 1,6 L A7L 7 kW 1 AVR / Brush SI N0
ENGINE POWER  START  CYLINDER  OIL CAPACITY (L)  ALTERNATOR  NOMINAL POWER  POWER FACTOR (Cosp)  VOLTAGE REGULATION  LOW OIL PRESSURE  OVERLOAD INDICATOR  EMERGENCY BUTTON	Electric / Recoil 459 cc 1,6 L A7L 7 kW 1 AVR / Brush SI NO NO
ENGINE POWER  START  CYLINDER  OIL CAPACITY (L)  ALTERNATOR  NOMINAL POWER  POWER FACTOR (Cosφ)  VOLTAGE REGULATION  LOW OIL PRESSURE  OVERLOAD INDICATOR  EMERGENCY BUTTON  NET WEIGHT (kg)	Electric / Recoil 459 cc 1,6 L A7L 7 kW 1 AVR / Brush SI NO NO 79